

SHOCKPROOF DIAL INDICATORS

- Meet DIN878
- Shockproof
- Jeweled bearing
- Supplied with limit pointers and bezel clamp
- Optional accessory: backs (page 164~165), contact points (page 161~163)



2314-10A

SHOCK
PROOF

JEWELLED
BEARING

**INSPECTION
CERTIFICATE**
TRACEABLE TO NIST

| Code | Range | Graduation | Accuracy | Hysteresis | Range/rev | Dial reading | Remark |
|-------------|-------|------------|----------|------------|-----------|--------------|-----------|
| 2314-3FA * | 3mm | 0.01mm | 12μm | 3μm | 1mm | 0-100 | flat back |
| 2314-5FA * | 5mm | 0.01mm | 14μm | 3μm | 1mm | 0-100 | flat back |
| 2314-10FA * | 10mm | 0.01mm | 17μm | 3μm | 1mm | 0-100 | flat back |
| 2314-3A * | 3mm | 0.01mm | 12μm | 3μm | 1mm | 0-100 | lug back |
| 2314-5A * | 5mm | 0.01mm | 14μm | 3μm | 1mm | 0-100 | lug back |
| 2314-10A * | 10mm | 0.01mm | 17μm | 3μm | 1mm | 0-100 | lug back |

* Supplied with manufacturer inspection certificate traceable to NIST USA

