



# STRAIGHT SHANK DRILLS

DL105 SERIES

## HSS-E, STRAIGHT SHANK TWIST DRILLS


JOBBER

- HSS-E, SPIRALBOHRER mit ZYLINDERSCHAFT
- Forets HSS-E, queue cylindrique, Forme C, série courte
- PUNTE ELICOIDALI, GAMBO CILINDRICO, HSS - E


KURZ  
COURTE  
CORTA

► **Surface treatment** : Coloring(Gold color)  
 ► **Application** : Drilling stainless steels and difficult - to - cut materials such as titanium and inconel.

► **Oberflächenbehandlung** : Coloring(Goldfarbe)  
 ► **Verwendung** : Zum Bohren von rostfreien und austenitischen. Stählen, schwerzerspanbaren Werkstoffen wie Titan und Inconel.



under 1.6mm 1.6mm & over



Unit : mm

EDP No.	Drill Diameter D1	Flute Length L1	Overall Length L2
DL105010	1.0	12	34
DL105011	1.1	14	36
DL105012	1.2	16	38
DL105912	1.25	16	38
DL105013	1.3	16	38
DL105014	1.4	18	40
DL105015	1.5	18	40
DL105016	1.6	20	43
DL105017	1.7	20	43
DL105917	1.75	22	46
DL105018	1.8	22	46
DL105019	1.9	22	46
DL105020	2.0	24	49
DL105021	2.1	24	49
DL105022	2.2	27	53
DL105922	2.25	27	53
DL105023	2.3	27	53
DL105024	2.4	30	57
DL105025	2.5	30	57
DL105026	2.6	30	57
DL105027	2.7	33	61
DL105927	2.75	33	61
DL105028	2.8	33	61
DL105029	2.9	33	61
DL105030	3.0	33	61
DL105031	3.1	36	65

EDP No.	Drill Diameter D1	Flute Length L1	Overall Length L2
DL105032	3.2	36	65
DL105932	3.25	36	65
DL105033	3.3	36	65
DL105034	3.4	39	70
DL105035	3.5	39	70
DL105036	3.6	39	70
DL105037	3.7	39	70
DL105937	3.75	39	70
DL105038	3.8	43	75
DL105039	3.9	43	75
DL105040	4.0	43	75
DL105041	4.1	43	75
DL105042	4.2	43	75
DL105942	4.25	43	75
DL105043	4.3	47	80
DL105044	4.4	47	80
DL105045	4.5	47	80
DL105046	4.6	47	80
DL105047	4.7	47	80
DL105947	4.75	47	80
DL105048	4.8	52	86
DL105049	4.9	52	86
DL105050	5.0	52	86
DL105051	5.1	52	86
DL105052	5.2	52	86
DL105952	5.25	52	86

► TiN(DN105), TiCN(DX105) and TiAlN(DT105) are available on your request.

► NEXT PAGE

◎ : Excellent ○ : Good

ISO Material Description	P										M				K					
	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel		Stainless steel		Grey cast iron		Nodular cast iron		Malleable cast iron	
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25		21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	◎	◎	◎	○	◎	◎	○	○	○	○	○	◎	○	○	○	○	○	○	○	○

ISO Material Description	N										S						H				
	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys						Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc											15	30	25	38	34			55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400	550
Recommended	○	○	○						○							○					

# YG STRAIGHT SHANK DRILLS

## DL105 SERIES

HSS

### HSS-E, STRAIGHT SHANK TWIST DRILLS


JOBBER

- HSS-E, SPIRALBOHRER mit ZYLINDERSCHAFT
- Forets HSS-E, queue cylindrique, Forme C, série courte
- PUNTE ELICOIDALI, GAMBO CILINDRICO, HSS - E


KURZ  
COURTE  
CORTA

► **Surface treatment** : Coloring(Gold color)  
 ► **Application** : Drilling stainless steels and difficult - to - cut materials such as titanium and inconel.

► **Oberflächenbehandlung** : Coloring(Goldfarbe)  
 ► **Verwendung** : Zum Bohren von rostfreien und austenitischen. Stählen, schwerzerspanbaren Werkstoffen wie Titan und Inconel.



under 1.6mm 1.6mm & over



DIN 338
HSS-E
33°
h8
135°
P.276-277

Unit : mm

EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2
DL105053	5.3	52	86
DL105054	5.4	57	93
DL105055	5.5	57	93
DL105056	5.6	57	93
DL105057	5.7	57	93
DL105957	5.75	57	93
DL105058	5.8	57	93
DL105059	5.9	57	93
DL105060	6.0	57	93
DL105061	6.1	63	101
DL105062	6.2	63	101
DL105962	6.25	63	101
DL105063	6.3	63	101
DL105064	6.4	63	101
DL105065	6.5	63	101
DL105066	6.6	63	101
DL105067	6.7	63	101
DL105967	6.75	69	109
DL105068	6.8	69	109
DL105069	6.9	69	109
DL105070	7.0	69	109
DL105071	7.1	69	109
DL105072	7.2	69	109
DL105972	7.25	69	109
DL105073	7.3	69	109
DL105074	7.4	69	109

EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2
DL105075	7.5	69	109
DL105076	7.6	75	117
DL105077	7.7	75	117
DL105977	7.75	75	117
DL105078	7.8	75	117
DL105079	7.9	75	117
DL105080	8.0	75	117
DL105081	8.1	75	117
DL105082	8.2	75	117
DL105982	8.25	75	117
DL105083	8.3	75	117
DL105084	8.4	75	117
DL105085	8.5	75	117
DL105086	8.6	81	125
DL105087	8.7	81	125
DL105987	8.75	81	125
DL105088	8.8	81	125
DL105089	8.9	81	125
DL105090	9.0	81	125
DL105091	9.1	81	125
DL105092	9.2	81	125
DL105992	9.25	81	125
DL105093	9.3	81	125
DL105094	9.4	81	125
DL105095	9.5	81	125
DL105096	9.6	87	133

► TIN(DN105), TiCN(DX105) and TiAlN(DT105) are available on your request.

► NEXT PAGE

ISO Material Description	P										M				K					
	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel		Stainless steel		Grey cast iron		Nodular cast iron		Malleable cast iron	
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	13	23	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	◎	◎	◎	○	○	◎	○	○	○	○	○	◎	○	○	○	○	○	○	○	○

ISO Material Description	N										S						H				
	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys						Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550
Recommended	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

◎ : Excellent ○ : Good

i-ONE DRILLS

i-DREAM DRILLS

DREAM DRILLS -GENERAL

DREAM DRILLS -HIGH FEED

DREAM DRILLS -FLAT BOTTOM

DREAM DRILLS -INOX

DREAM DRILLS -ALU

DREAM DRILLS -CFRP

DREAM DRILLS -MQL

DREAM DRILLS for HIGH HARDENED STEELS

GENERAL CARBIDE DRILLS

MULTI-1 DRILLS

HPD DRILLS

GOLD-P DRILLS

SUPER-GP DRILLS

STRAIGHT SHANK DRILLS

TAPER SHANK DRILLS

NC-SPOTTING DRILLS

CENTER DRILLS

SPADE DRILLS

REAMERS

COUNTER SINKS

COUNTER BORES

TECHNICAL DATA



# STRAIGHT SHANK DRILLS

DL105 SERIES

## HSS-E, STRAIGHT SHANK TWIST DRILLS

JOBBER

- HSS-E, SPIRALBOHRER mit ZYLINDERSCHAFT
- Forets HSS-E, queue cylindrique, Forme C, série courte
- PUNTE ELICOIDALI, GAMBO CILINDRICO, HSS - E


KURZ  
COURTE  
CORTA

► **Surface treatment** : Coloring(Gold color)  
 ► **Application** : Drilling stainless steels and difficult - to - cut materials such as titanium and inconel.

► **Oberflächenbehandlung** : Coloring(Goldfarbe)  
 ► **Verwendung** : Zum Bohren von rostfreien und austenitischen. Stählen, schwerzerspanbaren Werkstoffen wie Titan und Inconel.



under 1.6mm 1.6mm & over



Unit : mm

EDP No.	Drill Diameter D1	Flute Length L1	Overall Length L2
DL105097	9.7	87	133
DL105997	9.75	87	133
DL105098	9.8	87	133
DL105099	9.9	87	133
DL105100	10.0	87	133
DL105102	10.2	87	133
DL105105	10.5	87	133
DL105110	11.0	94	142
DL105115	11.5	94	142
DL105120	12.0	101	151
DL105125	12.5	101	151
DL105130	13.0	101	151
DL105135	13.5	108	160

EDP No.	Drill Diameter D1	Flute Length L1	Overall Length L2
DL105140	14.0	108	160
DL105145	14.5	114	169
DL105150	15.0	114	169
DL105155	15.5	120	178
DL105160	16.0	120	178
DL105165	16.5	125	184
DL105170	17.0	125	184
DL105175	17.5	130	191
DL105180	18.0	130	191
DL105185	18.5	135	198
DL105190	19.0	135	198
DL105195	19.5	140	205
DL105200	20.0	140	205

► TiN(DN105), TiCN(DX105) and TiAlN(DT105) are available on your request.

◎ : Excellent ○ : Good

ISO	P										M				K					
	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel		Stainless steel		Grey cast iron		Nodular cast iron		Malleable cast iron	
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25		21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	◎	◎	◎	○	○	◎	○	○	○	○	○	◎	○	○	○	○	○	○	○	○

ISO	N					S										H					
	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc											15	30	25	38	34			55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400	550
Recommended	○	○	○						○							○					



# STRAIGHT SHANK DRILLS

## RECOMMENDED CUTTING CONDITIONS EMPFOLHENE SCHNEIDPARAMETER

**D2107, D1107, D2105, DL105, D1105, D1125, D2104, D1121, DL109** SERIES

**HSS, HSS-E & HSSCo8  
COBALT DRILLS**

RPM = rev./min.  
FEED = mm/rev.

i-ONE DRILLS

i-DREAM DRILLS

DREAM DRILLS -GENERAL

DREAM DRILLS -HIGH FEED

DREAM DRILLS -FLAT BOTTOM

DREAM DRILLS -INOX

DREAM DRILLS -ALU

DREAM DRILLS -CFRP

DREAM DRILLS -MQL

DREAM DRILLS for HIGH HARDENED STEELS

GENERAL CARBIDE DRILLS

MULTI-1 DRILLS

HPD DRILLS

GOLD-P DRILLS

SUPER-GP DRILLS

STRAIGHT SHANK DRILLS

TAPER SHANK DRILLS

NC-SPOTTING DRILLS

CENTER DRILLS

SPADE DRILLS

REAMERS

COUNTER SINKS

COUNTER BORES

TECHNICAL DATA

ISO	VDI 3323	Material Description	Vc (m/min)	Parameter	Drill Diameter (mm)					
					2.0	3.0	4.0	6.0	8.0	
<b>P</b>	1	Non-alloy steel	30	RPM FEED	4770 0.02~0.04	3180 0.03~0.05	2390 0.04~0.06	1590 0.05~0.08	1190 0.10~0.13	
	2		25	RPM FEED	3980 0.02~0.04	2650 0.03~0.05	1990 0.04~0.06	1330 0.05~0.08	990 0.10~0.13	
	3		20	RPM FEED	3180 0.02~0.04	2120 0.03~0.05	1590 0.04~0.06	1060 0.05~0.08	800 0.10~0.13	
	4		20	RPM FEED	3180 0.01~0.02	2120 0.01~0.03	1590 0.02~0.04	1060 0.02~0.05	800 0.03~0.06	
	5									
	6	Low alloy steel	25	RPM FEED	3980 0.02~0.04	2650 0.03~0.05	1990 0.04~0.06	1330 0.05~0.08	990 0.10~0.13	
	7		20	RPM FEED	3180 0.02~0.04	2120 0.03~0.05	1590 0.04~0.06	1060 0.05~0.08	800 0.10~0.13	
	8		20	RPM FEED	3180 0.01~0.02	2120 0.01~0.03	1590 0.02~0.04	1060 0.02~0.05	800 0.03~0.06	
	9									
	10		High alloyed steel, and tool steel	15	RPM FEED	2390 0.02~0.04	1590 0.03~0.05	1190 0.04~0.06	800 0.05~0.08	600 0.10~0.13
	11									
<b>M</b>	12	Stainless steel	20	RPM FEED	3180 0.02~0.04	2120 0.03~0.05	1590 0.04~0.06	1060 0.05~0.08	800 0.10~0.13	
	13		15	RPM FEED	2390 0.02~0.04	1590 0.03~0.05	1190 0.04~0.06	800 0.05~0.08	600 0.10~0.13	
	14		10	RPM FEED	1590 0.01~0.02	1060 0.01~0.03	800 0.02~0.04	530 0.02~0.05	400 0.03~0.06	
<b>K</b>	15	Grey cast iron	30	RPM FEED	4770 0.02~0.04	3180 0.03~0.05	2390 0.04~0.06	1590 0.05~0.08	1190 0.10~0.13	
	16		25	RPM FEED	3980 0.01~0.02	2650 0.01~0.03	1990 0.02~0.04	1330 0.02~0.05	990 0.03~0.06	
	17	Nodular cast iron	30	RPM FEED	4770 0.02~0.04	3180 0.03~0.05	2390 0.04~0.06	1590 0.05~0.08	1190 0.10~0.13	
	18									
	19	Malleable cast iron	25	RPM FEED	3980 0.02~0.04	2650 0.03~0.05	1990 0.04~0.06	1330 0.05~0.08	990 0.10~0.13	
20										
<b>N</b>	21	Aluminum-wrought alloy	55	RPM FEED	8750 0.03~0.06	5840 0.05~0.09	4380 0.07~0.11	2920 0.12~0.16	2190 0.12~0.18	
	22		55	RPM FEED	8750 0.03~0.06	5840 0.05~0.09	4380 0.07~0.11	2920 0.12~0.16	2190 0.12~0.18	
	23	Aluminum-cast, alloyed	40	RPM FEED	6370 0.03~0.06	4240 0.05~0.09	3180 0.07~0.11	2120 0.12~0.16	1590 0.12~0.18	
	24									
	25									
	26									
	27		Copper and Copper Alloys (Bronze / Brass)							
28										
29	Non Metallic Materials	20	RPM FEED	3180 0.02~0.04	2120 0.03~0.05	1590 0.04~0.06	1060 0.05~0.08	800 0.10~0.13		
30										
<b>S</b>	31	Heat Resistant Super Alloys								
	32									
	33									
	34									
	35									
	36	Titanium Alloys	10	RPM FEED	1590 0.01~0.03	1060 0.02~0.04	800 0.03~0.05	530 0.04~0.07	400 0.05~0.08	
	37									
<b>H</b>	38	Hardened steel								
	39									
	40		Chilled Cast Iron							
	41			Hardened Cast Iron						



# STRAIGHT SHANK DRILLS

## RECOMMENDED CUTTING CONDITIONS EMPFOHLENE SCHNEIDPARAMETER

HSS

RPM = rev./min.  
FEED = mm/rev.

VDI 3323	Parameter	Drill Diameter (mm)					
		10.0	13.0	16.0	18.0	20.0	30.0
1	RPM	950	730	600	530	480	320
	FEED	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
2	RPM	800	610	500	440	400	270
	FEED	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
3	RPM	640	490	400	350	320	210
	FEED	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
4	RPM	640	490	400	350	320	210
	FEED	0.03~0.06	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18
5							
6	RPM	800	610	500	440	400	270
	FEED	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
7	RPM	640	490	400	350	320	210
	FEED	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
8	RPM	640	490	400	350	320	210
	FEED	0.03~0.06	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18
9							
10	RPM	480	370	300	270	240	160
	FEED	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
11							
12	RPM	640	490	400	350	320	210
	FEED	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
13	RPM	480	370	300	270	240	160
	FEED	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
14	RPM	320	240	200	180	160	110
	FEED	0.03~0.06	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18
15	RPM	950	730	600	530	480	320
	FEED	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
16	RPM	800	610	500	440	400	270
	FEED	0.03~0.06	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18
17	RPM	950	730	600	530	480	320
	FEED	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
18							
19	RPM	800	610	500	440	400	270
	FEED	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
20							
21	RPM	1750	1350	1090	970	880	580
	FEED	0.14~0.20	0.16~0.22	0.18~0.24	0.20~0.28	0.20~0.30	0.28~0.38
22	RPM	1750	1350	1090	970	880	580
	FEED	0.14~0.20	0.16~0.22	0.18~0.24	0.20~0.28	0.20~0.30	0.28~0.38
23	RPM	1270	980	800	710	640	420
	FEED	0.14~0.20	0.16~0.22	0.18~0.24	0.20~0.28	0.20~0.30	0.28~0.38
24							
25							
26							
27							
28							
29	RPM	640	490	400	350	320	210
	FEED	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
30							
31							
32							
33							
34							
35							
36	RPM	320	240	200	180	160	110
	FEED	0.05~0.09	0.06~0.10	0.05~0.11	0.06~0.12	0.09~0.13	0.12~0.18
37							
38							
39							
40							
41							

i-ONE DRILLS

i-DREAM DRILLS

DREAM DRILLS -GENERAL

DREAM DRILLS -HIGH FEED

DREAM DRILLS -FLAT BOTTOM

DREAM DRILLS -INOX

DREAM DRILLS -ALU

DREAM DRILLS -CFRP

DREAM DRILLS -MQL

DREAM DRILLS for HIGH HARDENED STEELS

GENERAL CARBIDE DRILLS

MULTI-1 DRILLS

HPD DRILLS

GOLD-P DRILLS

SUPER-GP DRILLS

STRAIGHT SHANK DRILLS

TAPER SHANK DRILLS

NC-SPOTTING DRILLS

CENTER DRILLS

SPADE DRILLS

REAMERS

COUNTER SINKS

COUNTER BORES

TECHNICAL DATA