



FLAT SHANK


E2595 SERIES

FLAT SHANK

EQ595 SERIES

HSSCo8, 4 FLUTE SHORT LENGTH - CENTER CUTTING

- **HSSCo8, 4&6 SCHNEIDEN KURZ**
- **Fraise HSSCo8, 4&6 dents, coupe au centre, courte**
- **4 - 6 TAGLIENTI, SERIE CORTA, TAGLIENTE AL CENTRO - HSSCo8**



HSS Co8

DIN 844

4

P.772~775

Unit : mm

EDP No.		Mill Diameter	Shank Diameter	Length of Cut	Overall Length
UNCOATED	TiAIN				
E2595020	EQ595020	2.0	6	7	51
E2595030	EQ595030	3.0	6	8	52
E2595040	EQ595040	4.0	6	11	55
E2595050	EQ595050	5.0	6	13	57
E2595060	EQ595060	6.0	6	13	57
E2595070	EQ595070	7.0	10	16	66
E2595080	EQ595080	8.0	10	19	69
E2595090	EQ595090	9.0	10	19	69
E2595100	EQ595100	10.0	10	22	72
E2595110	EQ595110	11.0	12	22	79
E2595120	EQ595120	12.0	12	26	83
E2595130	EQ595130	13.0	12	26	83
E2595140	EQ595140	14.0	12	26	83
E2595150	EQ595150	15.0	12	26	83
E2595160	EQ595160	16.0	16	32	92
E2595170	EQ595170	17.0	16	32	92
E2595180	EQ595180	18.0	16	32	92
E2595190	EQ595190	19.0	16	32	92
E2595200	EQ595200	20.0	16	38	98
E2595200	EQ595200	20.0	20	38	104
E2595220	EQ595220	22.0	20	38	104
E2595250	EQ595250	25.0	25	45	121

- ▶ Other shank design on your request.
- ▶ TiN and TiCN Coatings are available on your request.

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ + 0.04	h6

◎ : Excellent ○ : Good

ISO	P											M			K						
	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron	Malleable cast iron			
Material Description	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
VDI 3323																					
HRc	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25				
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230	
Recommend	◎	◎	◎	◎	◎	◎	◎	◎	○	◎	○										
ISO	N									S						H					
	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)		Non Metallic Materials		Heat Resistant Super Alloys						Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron	
Material Description	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
VDI 3323																					
HRc	60	100	75	90	130	110	90	100			15	30	25	38	34			55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550
Recommend	○	○	○	○	○																

E2595, E2596 SERIES


MULTI FLUTE - SIDE CUTTING

Vc = m/min.
fz = mm/tooth
RPM = rev./min.
FEED = mm/min.

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)						
						2.0	3.0	4.0	5.0	6.0	8.0	10.0
P	1	Non-alloy steel	0.1D	1.5D	Vc	35	35	35	35	35	35	35
					fz	0.004	0.008	0.013	0.02	0.025	0.036	0.045
					RPM	5570	3714	2785	2228	1857	1393	1114
	2		Vc	30	30	30	30	30	30	30		
			fz	0.003	0.006	0.011	0.017	0.023	0.036	0.044		
			RPM	4775	3183	2387	1910	1592	1194	955		
	3-4		Vc	25	25	25	25	25	25	25		
			fz	0.003	0.006	0.009	0.014	0.019	0.029	0.038		
			RPM	3979	2653	1989	1592	1326	995	796		
	5		Vc	15	15	15	15	15	15	15		
fz		0.002	0.005	0.01	0.014	0.019	0.029	0.036				
RPM		2387	1592	1194	955	796	597	477				
6	Vc	30	30	30	30	30	30	30				
	fz	0.003	0.006	0.011	0.017	0.023	0.036	0.044				
	RPM	4775	3183	2387	1910	1592	1194	955				
7	Vc	25	25	25	25	25	25	25				
	fz	0.003	0.006	0.009	0.014	0.019	0.029	0.038				
	RPM	3979	2653	1989	1592	1326	995	796				
8-9	Vc	15	15	15	15	15	15	15				
	fz	0.002	0.005	0.01	0.014	0.019	0.029	0.036				
	RPM	2387	1592	1194	955	796	597	477				
10	Vc	30	30	30	30	30	30	30				
	fz	0.003	0.006	0.011	0.017	0.023	0.036	0.044				
	RPM	4775	3183	2387	1910	1592	1194	955				
11.1	Vc	15	15	15	15	15	15	15				
	fz	0.002	0.005	0.01	0.014	0.019	0.029	0.036				
	RPM	2387	1592	1194	955	796	597	477				
N	21-22	Aluminum-wrought alloy	0.1D	1.5D	Vc	75	105	100	100	105	100	95
					fz	0.005	0.009	0.014	0.019	0.021	0.036	0.048
					RPM	11937	11141	7958	6366	5570	3979	3024
23-24	Aluminum-cast, alloyed	0.1D	1.5D	Vc	49	68	65	65	68	65	62	
				fz	0.005	0.009	0.014	0.019	0.021	0.036	0.048	
				RPM	7799	7215	5173	4138	3608	2586	1974	

※ The FEED, in long & extra long types, should be reduced by around 50%

▶ NEXT PAGE




E2595, E2596 SERIES

MULTI FLUTE - SIDE CUTTING

Vc = m/min.
fz = mm/tooth
RPM = rev./min.
FEED = mm/min.

VDI 3323	Parameter	Diameter (Ø)											
		12.0	14.0	16.0	18.0	20.0	22.0	25.0	28.0	30.0	32.0	36.0	40.0
1	Vc	35	35	35	35	35	35	35	35	35	35	35	35
	fz	0.061	0.069	0.079	0.079	0.089	0.1	0.1	0.067	0.067	0.067	0.065	0.071
	RPM	928	796	696	619	557	506	446	398	371	348	309	279
2	FEED	227	220	220	196	198	203	178	160	149	140	121	119
	Vc	30	30	30	30	30	30	30	30	30	30	30	30
	fz	0.056	0.057	0.071	0.08	0.089	0.089	0.091	0.06	0.059	0.06	0.06	0.068
3-4	RPM	796	682	597	531	477	434	382	341	318	298	265	239
	FEED	178	156	170	170	170	155	139	123	113	107	95	97
	Vc	25	25	25	25	25	25	25	25	25	20	25	25
5	fz	0.048	0.054	0.058	0.066	0.066	0.075	0.073	0.048	0.05	0.049	0.05	0.056
	RPM	663	568	497	442	398	362	318	284	265	199	221	199
	FEED	127	123	115	117	105	109	93	82	80	58	66	67
6	Vc	15	15	15	15	15	15	15	15	15	15	15	15
	fz	0.047	0.054	0.058	0.065	0.074	0.074	0.069	0.047	0.047	0.054	0.049	0.053
	RPM	398	341	298	265	239	217	191	171	159	149	133	119
7	FEED	75	74	69	69	71	64	53	48	45	48	39	38
	Vc	30	30	30	30	30	30	30	30	30	30	30	30
	fz	0.056	0.057	0.071	0.08	0.089	0.089	0.091	0.06	0.059	0.06	0.06	0.068
8-9	RPM	796	682	597	531	477	434	382	341	318	298	265	239
	FEED	178	156	170	170	170	155	139	123	113	107	95	97
	Vc	25	25	25	25	25	25	25	25	25	20	25	25
10	fz	0.048	0.054	0.058	0.066	0.066	0.075	0.073	0.048	0.05	0.049	0.05	0.056
	RPM	663	568	497	442	398	362	318	284	265	199	221	199
	FEED	127	123	115	117	105	109	93	82	80	58	66	67
11.1	Vc	15	15	15	15	15	15	15	15	15	15	15	15
	fz	0.047	0.054	0.058	0.065	0.074	0.074	0.069	0.047	0.047	0.054	0.049	0.053
	RPM	398	341	298	265	239	217	191	171	159	149	133	119
21-22	FEED	75	74	69	69	71	64	53	48	45	48	39	38
	Vc	95	95	100	100	100	95	95	95	105	100	100	100
	fz	0.057	0.06	0.066	0.074	0.075	0.08	0.088	0.061	0.061	0.06	0.061	0.06
23-24	RPM	2520	2160	1989	1768	1592	1375	1210	1080	1114	995	884	796
	FEED	575	518	525	523	477	440	426	395	408	358	324	286
	Vc	62	62	65	65	65	62	62	62	62	68	65	65
23-24	fz	0.057	0.06	0.066	0.074	0.075	0.08	0.088	0.061	0.061	0.06	0.061	0.06
	RPM	1645	1410	1293	1149	1035	897	789	705	722	647	575	517
	FEED	375	338	341	340	310	287	278	258	264	233	210	186



CBN END MILLS

i-Xmill END MILLS

i-SMART MODULAR END MILLS

X5070 END MILLS

4G MILL END MILLS

X-POWER PRO END MILLS

TitaNox-POWER END MILLS

JET-POWER END MILLS

V7 PLUS END MILLS

ALU-POWER HPC END MILLS

ALU-POWER END MILLS

D-POWER GRAPHITE END MILLS

D-POWER CFRP END MILLS

ROUTERS

CRX S END MILLS

K-2 END MILLS

ONLY ONE COATED PM60 END MILLS

TANK-POWER END MILLS

GENERAL HSS END MILLS

MILLING CUTTERS

TECHNICAL DATA

EQ595, EQ596 SERIES


MULTI FLUTE TiAlN COATED - RED CUTTING

Vc = m/min.
fz = mm/tooth
RPM = rev./min.
FEED = mm/min.

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)						
						2.0	3.0	4.0	5.0	6.0	8.0	10.0
P	1	Non-alloy steel	0.1D	1.5D	Vc	50	45	50	50	45	50	50
					fz	0.004	0.008	0.013	0.02	0.025	0.036	0.045
					RPM	7958	4775	3979	3183	2387	1989	1592
	2		Vc	40	40	40	40	40	40	40		
			fz	0.003	0.006	0.011	0.018	0.023	0.036	0.045		
			RPM	6366	4244	3183	2546	2122	1592	1273		
	3-4		Vc	35	35	30	35	30	30	35		
			fz	0.003	0.006	0.009	0.014	0.018	0.029	0.039		
			RPM	5570	3714	2387	2228	1592	1194	1114		
	5		Vc	20	20	20	20	20	20	20		
fz		0.002	0.004	0.01	0.014	0.019	0.028	0.035				
RPM		3183	2122	1592	1273	1061	796	637				
6	Vc	40	40	40	40	40	40	40				
	fz	0.003	0.006	0.011	0.018	0.023	0.036	0.045				
	RPM	6366	4244	3183	2546	2122	1592	1273				
7	Vc	35	35	30	35	30	30	35				
	fz	0.003	0.006	0.009	0.014	0.018	0.029	0.039				
	RPM	5570	3714	2387	2228	1592	1194	1114				
8-9	Vc	20	20	20	20	20	20	20				
	fz	0.002	0.004	0.01	0.014	0.019	0.028	0.035				
	RPM	3183	2122	1592	1273	1061	796	637				
10	Vc	40	40	40	40	40	40	40				
	fz	0.003	0.006	0.011	0.018	0.023	0.036	0.045				
	RPM	6366	4244	3183	2546	2122	1592	1273				
11.1	Vc	20	20	20	20	20	20	20				
	fz	0.002	0.004	0.01	0.014	0.019	0.028	0.035				
	RPM	3183	2122	1592	1273	1061	796	637				
N	21-22	Aluminum-wrought alloy	0.1D	1.5D	Vc	105	145	140	140	150	140	135
					fz	0.005	0.009	0.014	0.019	0.021	0.036	0.048
23-24	Aluminum-cast, alloyed	0.1D	1.5D	Vc	68	94	91	91	98	91	88	
				fz	0.005	0.009	0.014	0.019	0.021	0.036	0.048	

※ The FEED, in long & extra long types, should be reduced by around 50%

▶ NEXT PAGE



EQ595, EQ596 SERIES

MULTI FLUTE TiAIN COATED - SIDE CUTTING

Vc = m/min.
fz = mm/tooth
RPM = rev./min.
FEED = mm/min.

VDI 3323	Parameter	Diameter (Ø)											
		12.0	14.0	16.0	18.0	20.0	22.0	25.0	28.0	30.0	32.0	36.0	40.0
1	Vc	45	50	50	50	50	50	50	50	45	50	50	50
	fz	0.062	0.07	0.078	0.078	0.088	0.1	0.096	0.068	0.065	0.065	0.063	0.071
	RPM	1194	1137	995	884	796	723	637	568	477	497	442	398
2	FEED	296	318	310	276	280	289	244	232	186	194	167	170
	Vc	40	45	40	40	40	45	45	45	40	40	40	40
	fz	0.057	0.056	0.07	0.08	0.087	0.087	0.093	0.058	0.057	0.058	0.06	0.069
3-4	RPM	1061	1023	796	707	637	651	573	512	424	398	354	318
	FEED	242	229	223	226	222	227	213	178	145	138	127	132
	Vc	35	35	35	30	35	35	35	35	35	30	35	30
5	fz	0.047	0.053	0.056	0.066	0.066	0.073	0.069	0.046	0.05	0.05	0.047	0.057
	RPM	928	796	696	531	557	506	446	398	371	298	309	239
	FEED	175	169	156	140	147	148	123	110	111	90	87	82
6	Vc	20	20	20	20	20	20	20	20	20	20	15	20
	fz	0.048	0.053	0.056	0.064	0.075	0.075	0.07	0.054	0.054	0.054	0.056	0.056
	RPM	531	455	398	354	318	289	255	227	212	199	133	159
7	FEED	102	96	89	91	95	87	71	74	69	64	45	53
	Vc	40	45	40	40	40	45	45	45	40	40	40	40
	fz	0.057	0.056	0.07	0.08	0.087	0.087	0.093	0.058	0.057	0.058	0.06	0.069
8-9	RPM	1061	1023	796	707	637	651	573	512	424	398	354	318
	FEED	242	229	223	226	222	227	213	178	145	138	127	132
	Vc	35	35	35	30	35	35	35	35	35	30	35	30
10	fz	0.047	0.053	0.056	0.066	0.066	0.073	0.069	0.046	0.05	0.05	0.047	0.057
	RPM	928	796	696	531	557	506	446	398	371	298	309	239
	FEED	175	169	156	140	147	148	123	110	111	90	87	82
11.1	Vc	20	20	20	20	20	20	20	20	20	20	15	20
	fz	0.048	0.053	0.056	0.064	0.075	0.075	0.07	0.054	0.054	0.054	0.056	0.056
	RPM	531	455	398	354	318	289	255	227	212	199	133	159
21	FEED	102	96	89	91	95	87	71	74	69	64	45	53
	Vc	130	135	140	140	140	135	135	135	145	140	140	140
	fz	0.057	0.06	0.066	0.074	0.074	0.081	0.087	0.06	0.06	0.06	0.061	0.064
22	RPM	3448	3069	2785	2476	2228	1953	1719	1535	1538	1393	1238	1114
	FEED	786	737	735	733	660	633	598	552	554	501	453	428
	Vc	85	88	91	91	91	88	88	88	94	91	91	91
23	fz	0.057	0.06	0.066	0.074	0.074	0.081	0.087	0.06	0.06	0.06	0.061	0.064
	RPM	2255	2001	1810	1609	1448	1273	1120	1000	997	905	805	724
	FEED	514	480	478	476	429	413	390	360	359	326	294	278

